

BRASS SHELL KIT INSTRUCTIONS

- 1) THE BRASS CAP GOES BETWEEN THE BREECH BLOCK AND FLANGE (ALSO CALLED THE PAPER OR WAD CUTTER). IF YOU TAKE THE FLANGE OFF THE BLOCK AND ON THE BACK OF THE FLANGE THE RING IS EMPTY THIS IS WHERE YOU PLACE THE BRASS CAP OR DOUGHNUT. IF YOU LOOK AT YOUR FLANGE AND THE RING ON THE BACK IS A SOLID DOUGHNUT THEN YOU HAVE THE NEW STYLE FLANGE AND WILL NOT NEED TO USE THE BRASS CAP.
- 2) PUT THE MANUFACTURER'S SUGGESTED BLACK POWDER INTO THE CASINGS.
- 3) PUT THE BULLET IN THE CASING – SOME STYLES WILL FIT AND SOME WILL NOT.
- 4) IF YOUR BULLET DOESN'T FIT, THEN USE A FELT OR CARDBOARD WAD OVER THE POWDER IN THE CASE, AND SLIDE THE BULLET INTO THE CHAMBER.
- 5) PUT THE BRASS CASING BEHIND THE BULLET.
- 6) PUT THE CAP ONTO THE NIPPLE.
- 7) THE SHARPS IS READY TO FIRE.